



Modulight, Inc.

Document type:		Document number:	Version:	
Product Specification		TBD	1.0	
Document name:				
ML1408 PRODUCT SPECIFICATION				
Author:	Reviewer:	Approver:	Release date:	Pages:
Vilvi			02-03-2007	3

TECHNICAL SPECIFICATION ML1408

1 SCOPE

Modulight's ML1408 is a high-performance single-mode 1310 nm bare die laser product. The laser emits ≥ 100 mW pulsed power (10 μ s PW, 1% DC) at 1310 nm wavelength. ML1408 is designed to be used as light source in fiber optic test and measurement equipment.

2 ORDERING INFORMATION

ML1408

3 ELECTRO-OPTICAL CHARACTERISTICS¹

Parameter		Conditions	Min.	Typ.	Max	Units
Optical Power	P_o	$P_w = 10 \mu\text{s}; D/C = 1\%$	100			mW
Operating Current	I_{op}	$P_o = 100 \text{ mW}; P_w = 10 \mu\text{s}; D/C = 1\%$			300	mA
Operating Voltage	V_{op}	$P_{op} = 50 \text{ mW}, \text{ CW}$			2	V
Threshold Current	I_{th}	$P_w = 10 \mu\text{s}; D/C = 1\%$		32		mA
Series resistance	R_s	CW		3		Ω
Center Wavelength	λ	$P_w = 10 \mu\text{s}; D/C = 1\%$	1280		1330	nm
Delta Lambda 25	$\Delta\lambda$	$P_w = 10 \mu\text{s}; D/C = 1\%$			7	nm

4 ABSOLUTE MAXIMUM RATINGS²

Parameter	Symbol	Rating	Unit
LD reverse voltage	V_{RLD}	2	V
LD forward current	I_{FLD}	750 ³	mA
Lead soldering temperature (<10 s)	T_{SLD}	260	$^{\circ}\text{C}$
Operating case temperature	T_c	0-60 $^{\circ}\text{C}$	$^{\circ}\text{C}$
Storage temperature	T_{STG}	-40-85 $^{\circ}\text{C}$	$^{\circ}\text{C}$

5 SAFETY INFORMATION

- The laser light emitted from this laser diode is invisible and may be harmful to the human eye. Avoid eye exposure to the beam, both direct and reflected.
- Products are subject to the risks normally associated with sensitive electronic devices including static discharge, transients, and overload. Please take care of proper ESD protection prior to handling the products.
- These Modulight products are not intended for use in systems where product malfunction can reasonably be expected to result in personal injury.

¹ All parameters at 25 $^{\circ}\text{C}$

² Operation in excess of any one of these parameters may result in permanent damage.

³ DC $\leq 1\%$, PW $\leq 10 \mu\text{s}$



Modulight, Inc.

Tel. +358 20 743 9000, Fax +358 20 743 9009
P.O.Box 770, FIN-33101 Tampere, FINLAND
www.modulight.com



Peak power and wavelength are for safety analysis
only do not present device performance

6 LIABILITY NOTE

- This document is sole property of Modulight, Inc. No part of this document may be copied without written acceptance of Modulight, Inc.
- All statements related to the products herein are believed to be reliable and accurate. However, the accuracy is not guaranteed and no responsibility is assumed for any inaccuracies or omissions. Modulight, Inc. reserves the right to make changes in the specifications at any time without prior notice.



Modulight, Inc.
Tel. +358 20 743 9000, Fax +358 20 743 9009
P.O.Box 770, FIN-33101 Tampere, FINLAND
www.modulight.com